

## Flexible and cost-efficient Solid Shine laser projector

Designed for single-screen projection and equipped with advanced collaboration technologies for education and corporate use



PT-MZ670 Series

	PT-MZ670/L	PT-MZ570/L	PT-MW630/L	PT-MW530/L
Resolution	WUXGA		WXGA	
Brightness	6,500 lm	5,500 lm	6,500 lm	5,500 lm
Contrast	3,000,000:1 *2			

Note: PT-MZ670L, PT-MZ570L, PT-MW630L, and PT-MW530L deliver the same performance as PT-MZ670, PT-MZ570, PT-MW630, and PT-MW530, but come without a lens.

### Brilliant Picture Quality

- SOLID SHINE Laser Phosphor Drive with LCD Optical Engine Delivers Bright, Vivid, and Detailed Picture Quality
- High Brightness of Up to 6,500 lm\*1 from a Compact and Lightweight Body
- Dynamic 3,000,000:1 Contrast\*2 Assures Excellent Text Legibility and Improved Picture Quality Realized by Laser Light Source
- Available in WUXGA\*3 for Crisp High-Resolution Image Reproduction
- Detail Clarity Processor 4 Enhances Image Clarity and Sharpness
- Daylight View Basic Ensures Clear and Vivid Images in Bright Environments
- DICOM Simulation Mode\*4 for Medical Presentations
- Color Adjustment Function Corrects Color Variations in Multiple-Projection

### Low Maintenance with ECO Functions

- Continuous Operational Period for Laser Light Source (Without Exchange) Extended to 20,000 Hours\*5\*6
- Inorganic LCD Panel and Inorganic Polarizing Plate Maintain High-Quality Images for Extended Period of Time
- Estimated Maintenance for Reusable ECO Filter Extended to Approx. 20,000 Hours\*6
- One-Way Airflow Design Enhances Lens Assembly Sealing to Reduce Dust Intrusion
- Dust-Resistant Cabinet Improves Sealing of Filter Module and Air-Intake Duct
- ECO Management System Effectively Reduces Power Consumption
- Ultra-Quiet 28 dB\*7 Operation in Quiet Mode

### Excellent System Flexibility

- DIGITAL LINK Supports Transmission of Uncompressed Full HD Video, Audio, and Control Commands Through a Single CAT 5e or Higher STP Cable for Distances of Up to 150 m (492 ft)\*8
- Powered Lens Shift, Zoom, and Focus via Remote Control
- Wireless Projection with Optional Module (ET-WM300)
- Corner Keystone & Curved Screen Correction
- Free 360-degree Projector Cabinet Rotation
- PT-EZ770 Series Lenses to Suit Various Rooms and Applications
- Network Function via LAN for Stress-free Remote Operation
- Supports Multi Monitoring & Control Software (Free)

\*1 PT-MZ670/L and PT-MW630/L only. Please refer chart above for brightness of each model. \*2 With image mode set to Dynamic. \*3 For PT-MZ670/L and PT-MZ570/L only. Please refer chart above for resolution of each model. \*4 This product is not a medical instrument. Do not use for actual medical diagnosis. \*5 Around this time, original light source brightness will have decreased by approximately 50%. \*6 For anticipated usage in general classrooms and meeting rooms. Estimated maintenance time varies depending on environment. \*7 33 dB in Normal/ECO Mode. \*8 150 m (492 ft) transmission available in Long Reach Mode with optional ET-YFB200G DIGITAL LINK Switcher only. Signal resolution is limited to 1080/60p (dot-clock frequency 148.5 MHz) and below.

## Specifications (Tentative)

Model	PT-MZ670/L	PT-MZ570/L	PT-MW630/L	PT-MW530/L
Power supply	100–240 V AC, 50/60 Hz			
Power consumption	TBD			
LCD panel	Panel size	19.3 mm (0.76") diagonal (16:10 aspect ratio)		
	Display method	Transparent LCD panel (× 3, R/G/B)		
	Drive method	Active matrix		
	Pixels	2,304,000 (1920 × 1200) × 3, total of 6,912,000 pixels		
Lens	PT-MZ670/MZ570/MW630/MW530: Powered zoom (Throw Ratio 1.7–2.8 :1), F = 1.7–2.3, f = 26.9–45.5 mm PT-MZ670L/MZ570L/MW630L/MW530L: Optional powered zoom/focus lenses			
Light source	Laser diode			
Screen size (diagonal)	1.03–10.57 m (40–400 in), 16:10 aspect ratio			
Brightness*1	6,500 lm	5,500 lm	6,500 lm	5,500 lm
Center-to-corner uniformity*1	90 %			
Contrast	3,000,000:1 (Dynamic Contrast)			
Resolution	1920 × 1200 pixels*2			1280 × 800 pixels*3
Scanning frequency	HDMI/DIGITAL LINK	Dot clock: 25–162 MHz (VGA: 640 × 480 pixels to WUXGA: 1920 × 1200 pixels, VESA CVT-RB compliant with HDCP).		
	RGB	fh: 15 kHz–91 kHz, fv: 24 Hz–100 Hz, dot clock: up to 162 MHz		
	YPbPr (Y/Cs/Cr)	fh: 15.73 kHz, fv: 59.94 Hz [480i (525i)], fh: 15.63 kHz, fv: 50 Hz [576i (625i)], fh: 45.00 kHz, fv: 60 Hz [720 (750)/60p], fh: 33.75 kHz, fv: 60 Hz [1080 (1125)/60i], fh: 28.13 kHz, fv: 25 Hz [1080 (1125)/25p], fh: 27.00 kHz, fv: 48 Hz [1080 (1125)/24F], fh: 67.50 kHz, fv: 60 Hz [1080 (1125)/60p], fh: 31.47 kHz, fv: 59.94 Hz [480p (525p)], fh: 31.25 kHz, fv: 50 Hz [576p (625p)], fh: 37.50 kHz, fv: 50 Hz [720 (750)/50p], fh: 28.13 kHz, fv: 50 Hz [1080 (1125)/50i], fh: 27.00 kHz, fv: 24 Hz [1080 (1125)/24p], fh: 33.75 kHz, fv: 30 Hz [1080 (1125)/30p], fh: 56.25 kHz, fv: 50 Hz [1080 (1125)/50p]		
	Video/YC	fh: 15.73 kHz, fv: 59.94 Hz [NTSC/NTSC4.43/PAL-M/PAL60], fh: 15.63 kHz, fv: 50 Hz [PAL/PAL-N/SECAM]		
Optical axis shift	Vertical (from center of screen)	±67 % (powered)		
	Horizontal (from center of screen)	±35 % (powered)		
Keystone correction range*3	Vertical: ±30 °, horizontal: ±25 °		Vertical: ±35 °, horizontal: ±35 ° (Up to a total of ±55 ° during simultaneous horizontal and vertical correction)	
Installation	Horizontal/Vertical, free 360-degree installation			
Built-in speaker	10 W (monaural)			
Terminals	HDMI IN	HDMI 19-pin × 2 (Deep Color, compatible with HDCP), audio signal: Linear PCM (Sampling frequency: 48 kHz/44.1 kHz/32 kHz)		
	RGB 1 IN	BNC × 5 (RGB or YPbPr/YCaCr × 1)		
	RGB 2 IN	D-sub HD 15-pin (female) × 1 (compatible with component input)		
	VIDEO IN	Pin jack × 1 (composite video)		
	MONITOR OUT	D-sub HD 15-pin (female) × 1 (RGB × 1) (compatible with RGB or YPbPr/YCaCr)		
	AUDIO IN	Pin jack × 2 (L/R × 1), M3 × 2 (L-R × 2)		
	AUDIO OUT	M3 × 1 (L-R × 1) for output (variable)		
	SERIAL IN	D-sub 9-pin (female) × 1 for external control (RS-232C compliant)		
	REMOTE 1 IN	D-sub 9-pin (female) × 1 for external control (parallel)		
	REMOTE 2 IN	M3 × 1 for wired remote control		
	LAN	RJ-45 × 1 for network connection, 10Base-T, 100Base-TX, compatible with PjLink™		
	DIGITAL LINK	RJ-45 × 1 for network and DIGITAL LINK connection, 100Base-TX, compatible with PjLink™, HDCP, Deep Color		
	Memory Viewer/Pairing	USB (Type A) × 1		
	DC OUT	USB (Type A) × 1, DC 5 V/2 A**		
Operating noise*4	33 dB (Normal/ECO Mode), 28 dB (Quiet Mode)			
Filter	x 1, estimated maintenance time: approx. 20,000 hours*5			
Cabinet materials	Molded plastic (PC + ABS)			
Dimensions (W × H × D)	PT-MZ670/MZ570/MW630/MW530: 560 × 205*6 × 443.2 mm (22 1/16" × 8 1/16" × 17 7/16") (with supplied lens)			
	PT-MZ670L/MZ570L/MW630L/MW530L: 560 × 205*6 × 428 mm (22 1/16" × 8 1/16" × 16 27/32") (without lens)			
Weight*7	PT-MZ670/MZ570/MW630/MW530: Approximately 16.0 kg (35.3 lbs) (with supplied lens) PT-MZ670L/MZ570L/MW630L/MW530L: Approximately 15.2 kg (33.5 lbs) (without lens)			
Operating environment	Operating temperature: 0 °C–45 °C (32 °F–113 °F)*8, operating humidity: 20 %–80 % (no condensation)			
Supplied accessories	Power cord with power cord holder*9, wireless/wired remote control unit × 1, batteries (R03/LR03/AAA type × 2), CD-ROM × 1 (operation manual)			

Note: The PT-MZ670L/MZ570L/MW630L/MW530L delivers the same performance as the PT-MZ670/MZ570/MW630/MW530, but comes without a lens.

\*1 Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards. \*2 Input signals that differ from supported resolution will be converted. \*3 With the supplied lens. Value differs when the correction for both directions is operated. \*4 No output when projector is on standby. \*5 For anticipated usage in general classrooms and meeting rooms. Estimated maintenance time varies depending on environment. \*6 With legs at shortest position. \*7 Average value. May differ depending on models. \*8 Brightness is limited at the operating temperature higher than 36 °C (96.8 °F) or at altitude higher than 1,400 m (4,593 ft) above sea level. \*9 Power cords available (x2) for Europe, the UK and Asia only.

## Optional Accessories

- Zoom Lens**  
 ET-ELW20 / ET-ELW22  
 ET-ELT20 / ET-ELT21/  
 ET-ELS20\*
  - DIGITAL LINK Switcher**  
 ET-YFB200G
  - Early Warning Software**  
 ET-SWA100 Series
  - Bracket Assembly**  
 ET-PKE300B
  - Wireless Module Unit**  
 ET-WM300
  - Digital Interface Box**  
 ET-YFB100G
  - Ceiling Mount Bracket**  
 ET-PKD120H (for high ceiling)  
 ET-PKD120S (for low ceiling)
  - Replacement Filter Unit**  
 ET-RFM100
  - Easy Wireless Stick**  
 ET-UW100\*
- \* Available only in the US and Europe. \* Availability varies depending on region.

- Fixed Lens**  
ET-ELW21

# Panasonic®

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability differs depending on region and country. This product may be subject to export control regulations. HDMI, the HDMI logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. PjLink™ is a registered trademark or pending trademark in Japan, the United States, and other countries and regions. All other trademarks are the property of their respective trademark owners. © 2017 Panasonic Corporation. All rights reserved.



For more information about Panasonic projectors, please visit:  
 Projector Global Website – [panasonic.net/cns/projector](http://panasonic.net/cns/projector)  
 Facebook – [www.facebook.com/panasonicprojector](https://www.facebook.com/panasonicprojector)  
 YouTube – [www.youtube.com/user/PanasonicProjector](https://www.youtube.com/user/PanasonicProjector)

All information included here is valid as of July 2017.

PT-MZ670PRE1 Printed in Japan.