UHZ68LV

Bright 4K UHD Dual Laser home entertainment projector







- 4K UHD dual-laser technology Immerse yourself in stunning visuals with 5000 lumens and 95% DCI-P3 colour accuracy
- Powered by Dolby Vision® and HDR10+ -Experience cinema-quality picture with incredible brightness, contrast, and colour
- PureEngine[™] Ultra Enjoy smooth motion, sharp details, and customised picture settings
- Flexible Installation Adapt to any space with 1.6x zoom, lens shift, and 360-degree projection



Elevate your home entertainment with the Optoma UHZ68LV 4K UHD Projector. Powered by Dolby Vision® and HDR10+ technologies, this dual-laser projector delivers stunning picture quality with incredible brightness, contrast, and colour accuracy.

Enjoy smooth motion, sharp details and customised picture settings with PureEngine™ Ultra. Watch films as the director intended with Filmmaker mode. Plus, with flexible installation options and long-lasting performance, the UHZ68LV is the perfect choice for any home cinema enthusiast.

Specifications

UPC: 796435 81 530 1, EAN: 50	055387668652 , Colour: Black
Display/image	
Display technology	DLP®
Resolution	UHD (3840x2160)
Brightness	5,000 lumens
Contrast ratio	3,200,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9
Keystone correction - horizontal	+/-30°
	+/-30°
Keystone correction - vertical Horizontal scan rate	+/-30 15 ~ 255Khz
/ertical scan rate	24 ~ 240Hz
Jniformity	24 ~ 240HZ 85%
Screen size	0.78m ~ 7.65m (30.6" ~ 301.1") diagonal
Lamp info	Laser
Light source type LASER life	
Optical	30,000 hours
Optical Throw ratio	1.2:1 ~ 1.92:1
Projection distance (m)	1.2.1 ~ 1.92.1 1m - 10m
Zoom	1.6
Zoom type	Manual
Focal length (mm)	17.63mm~27.88mm/0.694"~1.097"
Lens shift	Vertical -106 ~ 126%, Horizontal10 ~ 10%
Native offset	126%
Lens shift	Yes - see product downloads for more information
Connectivity	Tes see product downloads for more information
Connections	Increase 1 of LIDMU 0.1, 0 of LIDMU 0.0 (aADO)
	Inputs 1 x HDMI 2.1, 2 x HDMI 2.0 (eARC)
	Outputs 1 x USB-A power 1.5A, 2 x USB-A power 0.9A, 1 x 3D sync, 1 x Audio 3.5mm, 1 x S/PDIF
	Control 1 x RJ45, 1 x RS232, 2 x 12V trigger
General	
Noise level (min)	25dB
Noise level (max)	31dB
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian,
	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian,
	Chinese (simplified), Spanish, Swedish, Chinese (traditional),
	Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	0°C~40°C/32°F~104°F, max. altitude 3,048m/10,000ft, max.
	humidity operating 80%, non-operating 90%
Speaker count	2
Watts per speaker	5W
nput lag	8.50ms
Networking	
-	Yes
_AN - control	
_AN - control Power	
_AN - control Power Power supply	100 ~ 240V, 50 ~ 60Hz
_AN - control Power Power supply Power consumption (standby)	0.5W
LAN - control Power Power supply Power consumption (standby)	
LAN - control Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max)	0.5W
LAN - control Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	0.5W 165W
LAN - control Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H) mm	0.5W 165W
LAN - control Power Power supply Power consumption (standby) Power consumption (min)	0.5W 165W 345W



Copyright © 2025, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 26062025114049