

ZK708T

High brightness compact 4K UHD professional laser projector



- **7000 lumen 4K UHD projector - High brightness and compact for multiple professional environments**
- **Long life DuraCore laser technology - Delivers 30,000 hours of virtually maintenance free operation**
- **Dust resistant - Independently tested, IP6X certified**
- **Control flexibility of HDBaseT 3.0 - 4K, HDR and HLG compatibility**



At 7000 lumens, with 4K and HDR compatibility, the ZK708T combines a long-lifetime light source of up to 30,000 hours and an independent IP6X certified optical engine for 24/7 operation, offering truly maintenance-free projection. Added features include manual horizontal and vertical lens shift and built-in 15W speakers.

Specifications

UPC: 796435 44 718 2, EAN: 5055387667792, Colour: White

Display/image	
Display technology	DLP
Resolution	UHD (3840x2160)
Brightness	7,000 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Displayable colours (millions)	1073.4
Horizontal scan rate	5k~140kHzKhz
Vertical scan rate	24~120HzHz
Uniformity	85%
Screen size	0.8m ~ 7.67m (31.5" ~ 301.8") diagonal
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	1.2:1 ~ 1.92:1
Projection distance (m)	1.3m - 7.8m
Zoom	1.6
Zoom type	Manual
Focal length (mm)	17.63 ~ 27.9
Lens shift	Vertical -106 ~ 126%, Horizontal: +/-10%
Native offset	106%
Lens shift	Yes - see product downloads for more information
Connectivity	
Connections	Inputs 2 x HDMI 2.0, 2 x VGA, 2 x Audio 3.5mm, 1 x USB-A power 1.5A Outputs 1 x HDMI 2.0, 1 x Audio 3.5mm, 1 x 3D sync, 1 x 12V trigger Control 1 x HDBaseT 4K, 1 x RJ45, 1 x RS232
LAN - wireless networking	No
General	
Noise level (min)	33dB
Noise level (max)	36dB
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Remote control	Backlit ProAV remote
Heat dissipation	883BTU/hour
Speaker count	2
Watts per speaker	15W
In the box	AC power cord Remote control 2x AAA batteries Quick Start Guide
Networking	
LAN - control	Yes
LAN - wireless networking	No
LAN	Yes
Power	
Power supply	Universal AC 100--240V± 10%~ 50 / 60 Hz with PFC input
Power consumption (standby)	<0.5W
Power consumption (min)	300W
Power consumption (max)	366W
Weight and dimensions	
Dimensions (W x D x H) mm	374 x 302 x 117
Gross weight	8.6 kg
Net weight	6.3 kg

